

H38N

Full-function Through-the-wall ATM

H38N, a full-function ATM, offers the widest range of options, including cash withdrawal, cash and cheque deposit, passbook update, A4 statement printing and other value-added services.

With optional single note acceptor, H38N can be customized as a currency exchange machine. Bulk-note acceptance further strengthens its versatility and availability.



H38N Full-function Through-the-wall ATM

SPECIFICATIONS

Industrial PC

- ◆ Pentium 4 2.8 GHz or higher CPU, 512MB or more RAM, 80GB or higher HDD, DVD-RW

Display

- ◆ 15" TFT color LCD with 2x4 function display keypads
- ◆ 15" TFT color LCD with touch screen (optional)
- ◆ Privacy display filter (optional)
- ◆ Sunlight viewable TFT LCD (optional)
- ◆ Digitized voice guidance

Keypad

- ◆ Tactile 4 X 4 numeric metal keypad with English keys of "ENTER", "CLEAR", "CANCEL", local language keys are optional
- ◆ 2x4 function display keys
- ◆ PCI EPP
- ◆ Vandal resistant & dust proof
- ◆ Beep responding on key press

Lead-through Indicator

- ◆ Card reader indicator
- ◆ Receipt printer indicator
- ◆ Cash output indicator
- ◆ Envelope deposit indicator (optional)

Operator Interface

- ◆ ATM Status Indicator
- ◆ Operator Service Panel
- ◆ E-journal output to DVD-RW

Card Reader/Writer

- ◆ Motorized card reader/writer (magnetic/smart card, Hi-Co track 1/2/3 read and write, EMV certified.)
- ◆ Card capture capability
- ◆ Anti-fishing/skimming security features (optional)
- ◆ Card return on power failure (optional)
- ◆ Contactless smart card reader/writer (optional)
- ◆ DIP card reader/writer (optional)

Barcode Scanner (Optional)

- ◆ Single-string laser scanning
- ◆ International standard barcode support (CODE39, CODE128, etc.)
- ◆ Maximum scanning distance: 203mm

Printer

- ◆ Graphics Receipt Printer
 - High-speed graphics thermal printer
 - Local character printing
 - Mini statement printing (optional)
- ◆ Journal Printer
 - Dot matrix or thermal printer
- ◆ A4 statement printer (optional)
- ◆ Passbook printer (optional)
- ◆ Extra media printer (optional)

Envelope Deposit (Optional)

- ◆ Motorized envelope feeding
- ◆ Integrated dot matrix printer
- ◆ Envelope capacity: Max. 100 bank notes per envelope
- ◆ Envelope depository bin capacity:
 - Approximate 100 envelopes with 15 notes per envelope

Cash Acceptor (Optional)

- ◆ Accepts and validates up to 100 notes per transaction
- ◆ Storage up to 1500 notes
- ◆ Accepting speed: 6 notes per second
- ◆ Category of identified currency: 177

Check Processor (Optional)

- ◆ True MICR read of E13B or CMC7 code line
- ◆ Front and Rear imaging of documents
- ◆ Inkjet rear side endorsement
- ◆ Double feed detection and document alignment in paper path
- ◆ USB2.0 communication

Dispenser

- ◆ High-speed dispenser
 - Frictional bundle-cash dispensing
 - Dispensing speed: 7 notes per second
 - Maximum 60 notes per bundle
 - Note Cassette: standard 2, maximum 4
 - 1 Reject Vault, separately retract and divert compartment
 - Note Cassette capacity: inner length 350 mm (13.8 in.), approximately 3000 new notes
 - Universal media size range support
 - Reject Vault capacity: Max. 250 notes (bundle reject) + 100 notes (single reject)

Security

- ◆ Physical:
 - UL291 Standard Level 1 safe
 - Dial combination lock plus mechanical lock
- ◆ PCI EPP
- ◆ EMV Level 2 certified
- ◆ Consumer awareness mirror
- ◆ DVR surveillance system (optional): video capture triggered by timing, alarm, transaction or motion detecting
- ◆ Transaction image capture for surveillance (optional)

Software

- ◆ Operating system: Windows XP Pro
- ◆ ATM application software:
 - NDC/NDC+ emulation
 - DDC emulation
 - ISO8583 emulation
 - Standard CEN/XFS SP
 - Can be customized to comply with any ATM switching system

Network Communication

- ◆ Standard TCP/IP, leased line connection
- ◆ PSTN dial-up connection (optional)
- ◆ Wireless connection (optional): GPRS/CDMA
- ◆ SNA/SDLC (optional)
- ◆ X.25 (optional)

Working Environment

- ◆ Operating temperature:
 - 32°F (0°C) to 122°F (50°C)
 - 31°F (-35°C) to 122°F (50°C) with thermostat unit
- ◆ Relative humidity: 20% to 95% non-condensing
- ◆ Thermostat Unit (optional)

Power Consumption

- ◆ AC110-120V~/220-240V~, 50-60Hz
- ◆ Idle: 160W
- ◆ Working: 255W
- ◆ UPS (optional)
 - 1KVA
 - Intelligent emergency power supply and power cut off alarm

Dimensions & Weight

- ◆ Height: 68.4in. (1736.5 mm)
- ◆ Width: 31.7 in. (805 mm)
- ◆ Depth: 45.9in. (1166 mm)
- ◆ Weight: 1764 lbs (800 kg)

GRG Banking Equipment Co., Ltd.

163 Pingyun Rd., West Huangpu Ave.,
Guangzhou City, China, 510656

Tel: +86-20-38204564 / 38699033

Fax: +86-20-38699014

E-mail: atm@grgbanking.com

Copyright by GRG Banking Equipment Co., Ltd.
All rights reserved.

Specifications are subject to update without prior notice.
Please consult GRG Banking or its representative for the latest information.

www.GRGBanking.com